

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 28.09.2020

Revision: 28.09.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** HADALAN EPUni 12E, Komp. A
- **Article number:** 40231A
- **UFI:** 9P50-K0AG-F005-GRNY
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Low-viscosity, solvent-free epoxy resin, component A (resin).
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Sievert Baustoffe GmbH & Co. KG
Mühlenschweg 6
D-49090 Osnabrück
Tel.: +49 2363 5663-0
- **Further information obtainable from:**
Abteilung: Produktsicherheit
Tel.: +49 2363 5663-0
info-hahne@sievert.de
- **1.4 Emergency telephone number:**
Giftinformationszentrum Nord (GIZ Nord) Universität Göttingen,
Tel.: 0551-19240

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2	H315 Causes skin irritation.
Eye Irrit. 2	H319 Causes serious eye irritation.
Skin Sens. 1	H317 May cause an allergic skin reaction.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS07



GHS09

- **Signal word** Warning
- **Hazard-determining components of labelling:**
reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.09.2020

Revision: 28.09.2020

Trade name: HADALAN EPUni 12E, Komp. A

(Contd. of page 1)

formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol oxirane, mono[(C12-14-alkyloxy)methyl] derivs

Hazard statements

- H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H317 May cause an allergic skin reaction.
 H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

- P262 Do not get in eyes, on skin, or on clothing.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 P360 Rinse immediately contaminated clothing and skin with plenty of water before removing clothes.

Additional information:

Contains epoxy constituents. May produce an allergic reaction.

2.3 Other hazards
Results of PBT and vPvB assessment

- **PBT:** Not applicable.
 · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures
Description:

Mixture of substances listed below with nonhazardous additions.

Epoxy resin

Dangerous components:

CAS: 25068-38-6 NLP: 500-033-5	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)	50-100%
	⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	
CAS: 9003-36-5	formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	10-25%
	⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317	
CAS: 68609-97-2 EINECS: 271-846-8	oxirane, mono[(C12-14-alkyloxy)methyl] derivs	10-25%
	⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317	

Additional information:

For the wording of the listed hazard phrases refer to section 16.

GISCODE: RE 1 (resin + hardener)

SECTION 4: First aid measures

4.1 Description of first aid measures
After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.09.2020

Revision: 28.09.2020

Trade name: HADALAN EPUni 12E, Komp. A

(Contd. of page 2)

- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
Use fire extinguishing methods suitable to surrounding conditions.
Use fire extinguishing methods suitable to surrounding.
Foam (alcohol resistant), carbon dioxide, dry powder, water spray
- **For safety reasons unsuitable extinguishing agents:** Water jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:**
No special measures required.
In case of fire: breathing protection with independent air supply.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Keep away non-protected persons. Ensure adequate ventilation.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
No special precautions are necessary if used correctly.
Only store in original containers
- **Information about fire - and explosion protection:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Keep cool and dry.
- **Information about storage in one common storage facility:** Store separate from eatables
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** VCI: 10
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.09.2020

Revision: 28.09.2020

Trade name: **HADALAN EPUni 12E, Komp. A**

(Contd. of page 3)

- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
 Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing
 Wash hands before breaks and at the end of work.
 Avoid contact with the eyes and skin.
- **Respiratory protection:**
 Not required.
 With good ventilation not necessary.
- **Protection of hands:**
 Protective gloves
 Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
 Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
 Use protective gloves. Wear Nitrile gloves with a thickness of min. 0.4 mm.
 (Breakthrough ³ 480 min. - See also www.gisbau.de.)
- **Material of gloves**
 The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
 The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:** Tightly sealed goggles
- **Body protection:** Use long-sleeved protective clothing.

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**

Form:	Fluid
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
- **pH-value:** n.a.
- **Change in condition**

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	>200 °C
- **Flash point:** 120 °C
- **Flammability (solid, gas):** Not applicable.
- **Ignition temperature:** 450 °C
- **Decomposition temperature:** Not determined.
- **Auto-ignition temperature:** Product is not selfigniting.
- **Explosive properties:** Product does not present an explosion hazard.
- **Explosion limits:**

Lower:	Not determined.
---------------	-----------------

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 28.09.2020

Revision: 28.09.2020

Trade name: **HADALAN EPUni 12E, Komp. A**

(Contd. of page 4)

Upper:	Not determined.
· Vapour pressure at 50 °C:	<5 hPa
· Density at 20 °C:	1.12 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic at 20 °C:	600 mPas
Kinematic:	Not determined.
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions**
Exothermic reactions with amines. Work quickly after adding the hardener, since at high curing temperatures can be achieved.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:**
Keep away from highly acidic and alkaline materials, oxidizing agents to avoid exothermic reactions.
- **10.6 Hazardous decomposition products:**
No dangerous decomposition products known.
At higher temperatures may produce carbon dioxide, carbon monoxide and nitrogen oxides.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)		
Dermal	LD50	>2,000 mg/kg (rab)
		>2,000 mg/kg (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation**
May cause an allergic skin reaction.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 28.09.2020

Revision: 28.09.2020

Trade name: **HADALAN EPUni 12E, Komp. A**

(Contd. of page 5)

· **Aspiration hazard** Based on available data, the classification criteria are not met.**SECTION 12: Ecological information**· **12.1 Toxicity**· **Aquatic toxicity:** No further relevant information available.· **12.2 Persistence and degradability** No further relevant information available.· **12.3 Bioaccumulative potential** No further relevant information available.· **12.4 Mobility in soil** No further relevant information available.· **Ecotoxicological effects:**· **Remark:** Toxic for fish· **Additional ecological information:**· **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

· **12.5 Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.· **12.6 Other adverse effects** No further relevant information available.**SECTION 13: Disposal considerations**· **13.1 Waste treatment methods**· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

· **Uncleaned packaging:**· **Recommendation:** Disposal must be made according to official regulations.**SECTION 14: Transport information**· **14.1 UN-Number**· **ADR, IMDG, IATA**

UN3082

· **14.2 UN proper shipping name**· **ADR**

3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700), phenol, polymer with formaldehyde, glycidyl ether)

· **IMDG**

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700), formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol), MARINE POLLUTANT

(Contd. on page 7)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 28.09.2020

Revision: 28.09.2020

Trade name: **HADALAN EPUni 12E, Komp. A**

(Contd. of page 6)

· IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700), formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol)
· 14.3 Transport hazard class(es) · ADR, IMDG, IATA	
 	
· Class · Label	9 Miscellaneous dangerous substances and articles. 9
· 14.4 Packing group · ADR	III
· 14.5 Environmental hazards: · Marine pollutant: · Special marking (ADR): · Special marking (IATA):	Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree)
· 14.6 Special precautions for user · Hazard identification number (Kemler code): · Stowage Category	Warning: Miscellaneous dangerous substances and articles. 90 A
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ) · Transport category · Tunnel restriction code	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml 3 E
· UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (REACTION PRODUCT: BISPHENOL-A-(EPICHLORHYDRIN) EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT = 700), PHENOL, POLYMER WITH FORMALDEHYDE, GLYCIDYL ETHER), 9, III

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- Directive 2012/18/EU
- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- National regulations:
- Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.09.2020

Revision: 28.09.2020

Trade name: HADALAN EPUni 12E, Komp. A

(Contd. of page 7)

· **Other regulations, limitations and prohibitive regulations**

For activities involving exposure to uncured epoxy resins and contact through the skin or the respiratory regular occupational medical examinations are to be taken.

The product subject to the directive 2004/42/EG. The VOC limit value of this product in ready to use condition is max. 500 g/l. The product contains in ready to use condition max. 1 g/l VOC.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 28.09.2020

Revision: 28.09.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** HADALAN EPUni 12E, Komp. B
- **Article number:** 40231B
- **UFI:** VS50-300V-R00P-5381
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture**
Solvent-free, low-viscosity epoxy resin, 2-component, component B (hardener).
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Sievert Baustoffe GmbH & Co. KG
Mühlenschweg 6
D-49090 Osnabrück
Tel.: +49 2363 5663-0
- **Further information obtainable from:**
Abteilung: Produktsicherheit
Tel.: +49 2363 5663-0
info-hahne@sievert.de
- **1.4 Emergency telephone number:**
Giftinformationszentrum Nord (GIZ Nord) Universität Göttingen,
Tel.: 0551-19240

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS05 corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.
Eye Dam. 1 H318 Causes serious eye damage.



GHS09 environment

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.
Skin Sens. 1 H317 May cause an allergic skin reaction.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.09.2020

Revision: 28.09.2020

Trade name: **HADALAN EPUni 12E, Komp. B**

(Contd. of page 1)

· **Hazard pictograms**

GHS05 GHS07 GHS09

· **Signal word** *Danger*· **Hazard-determining components of labelling:**

Carbomonocyclic alkylated mixtures of poly-aza-alkanes, hydrogenated
3-aminopropyldiethylamine
formaldehyde, oligomeric reaction products with phenol
1,3-benzenedimethanamine, N-(2-phenylethyl) derivs.

· **Hazard statements**

H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H410 Very toxic to aquatic life with long lasting effects.

· **Precautionary statements**

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

· **2.3 Other hazards**· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients
· **3.2 Chemical characterisation: Mixtures**· **Description:** Amine-containing hardener for epoxy resins· **Dangerous components:**

CAS: 1173092-74-4	Carbomonocyclic alkylated mixtures of poly-aza-alkanes, hydrogenated ⚠ Skin Corr. 1C, H314; ⚠ Aquatic Acute 1, H400; Aquatic Chronic 2, H411; ⚠ Acute Tox. 4, H302; Skin Sens. 1, H317	25-50%
CAS: 9003-35-4	formaldehyde, oligomeric reaction products with phenol ⚠ Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412	10-25%
CAS: 104-78-9 EINECS: 203-236-4	3-aminopropyldiethylamine ⚠ Flam. Liq. 3, H226; ⚠ Skin Corr. 1B, H314; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317	2.5-10%
CAS: 404362-22-7	1,3-benzenedimethanamine, N-(2-phenylethyl) derivs. ⚠ STOT RE 2, H373; ⚠ Skin Corr. 1B, H314; ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Acute Tox. 4, H302; Skin Sens. 1, H317	2.5-10%

· **Additional information:**

For the wording of the listed hazard phrases refer to section 16.
GISCODE: RE 1 (resin + hardener)

GB

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.09.2020

Revision: 28.09.2020

Trade name: **HADALAN EPUni 12E, Komp. B**

(Contd. of page 2)

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:**
Call for a doctor immediately.
Drink plenty of water and provide fresh air. Call for a doctor immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralising agent.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in the original container
- **Information about storage in one common storage facility:**
Do not store together with acids.
Store away from food, beverages and feed. Store in the original container
- **Further information about storage conditions:** Keep container tightly sealed.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 28.09.2020

Revision: 28.09.2020

Trade name: **HADALAN EPUni 12E, Komp. B**

(Contd. of page 3)

- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- **DNELs**

3-aminopropyl diethylamine

Average population Oral Long-term systemic effects; 0.08 mg / kg body weight / day

Repeated dose toxicity workers Dermal long-term systemic effects; 0.16 mg / kg

Body weight / day

Repeated dose toxicity worker inhalation Long-term local effects; 1.17 mg / m³

Respiratory tract irritation worker inhalation short-term - local; 2.34 mg / m³

Irritation of the respiratory tract Average population inhalation Long-term systemic effects; 0.29 mg / m³

Repeated dose toxicity worker inhalation Long-term systemic effects; 1.17 mg / m³

Repeated dose toxicity Average population short-term inhalation - local; 0.29 mg / m³

Average population eyes local effect; No data is available

Workers eyes local effect; High risk (no threshold derived)

Products from reactions of 1,3-benzenedimethanamine with styrene

Workers Dermal Long-term Systemic Effects; 0.05 mg / kg body weight / day

Repeated dose toxicity worker inhalation Long-term local effects; 0.004 mg / m³

Repeated dose toxicity Average population Dermal long-term systemic effects; 0.03 mg / kg

Body weight / day

Repeated dose toxicity Average population inhalation Long-term local effects; 0.002 mg / m³

Repeated dose toxicity worker inhalation Long-term systemic effects; 0.18 mg / m³

Repeated dose toxicity Average population inhalation Long-term systemic effects; 0.04 mg / m³

Repeated dose toxicity workers eyes local effect high hazard (no threshold derived)

Average population eyes local effect; High risk (no threshold derived)

Average population Oral Long-term systemic effects; 0.03 mg / kg body weight / day toxicity repeated doses

- **PNECs**

3-aminopropyl diethylamine

Sewage treatment plant 10 mg / l aquatic (sea water) 0.003 mg / l aquatic (fresh water) 0.03 mg / l

Sediment (sea water) 0.011 mg / kg sediment (fresh water) 0.115 mg / kg

Soil 0.005 mg / kg

Products from reactions of 1,3-benzenedimethanamine with styrene

Sediment (sea water) 0.014 mg / kg Aquatic (sea water) 0 mg / l Sediment (fresh water) 0.14 mg / kg

Sewage treatment plant 1 mg / l

Aquatic (freshwater) 0.001 mg / l predator 0.167 mg / kg oral

Soil 0.028 mg / kg

- **Additional information:** The lists valid during the making were used as basis.

- **8.2 Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

- **Protection of hands:**

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.09.2020

Revision: 28.09.2020

Trade name: HADALAN EPUni 12E, Komp. B

(Contd. of page 4)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:** Tightly sealed goggles

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· Form:	Fluid
· Colour:	According to product specification
· Odour:	aminic
· Odour threshold:	Not determined.

· **pH-value at 20 °C:** 11

· **Change in condition**

· Melting point/freezing point:	Undetermined.
· Initial boiling point and boiling range:	>200 °C

· **Flash point:** >100 °C

· **Flammability (solid, gas):** Not applicable.

· **Ignition temperature:** 435 °C

· **Decomposition temperature:** Not determined.

· **Auto-ignition temperature:** Product is not selfigniting.

· **Explosive properties:** Product does not present an explosion hazard.

· **Explosion limits:**

· Lower:	Not determined.
· Upper:	Not determined.

· **Vapour pressure at 21 °C:** >0 hPa

· Density at 20 °C:	1 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.

· **Solubility in / Miscibility with water at 20 °C:**

Es liegen keine Daten vor

· **Partition coefficient: n-octanol/water:** Not determined.

· **Viscosity:**

· Dynamic at 20 °C:	500 mPas
· Kinematic:	Not determined.

· **9.2 Other information** No further relevant information available.

GB

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.09.2020

Revision: 28.09.2020

Trade name: **HADALAN EPUni 12E, Komp. B**

(Contd. of page 5)

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
 - Swallow
 - Product: No data is available on the product itself.
 - Components:
 - Carbomonocyclic, alkylated mixtures of poly-aza-alkanes, hydrogenated LD 50 (rat): 500 mg / kg
 - Phenol, polymer with formaldehyde LD 50 (rat, male and female): > 5,000 mg / kg Due to the available data, the classification criteria are not met.
 - 3-aminopropyldiethylamine: No data available.
 - Products from reactions of 1,3-benzenedimethanamine with styrene: No data available.
 - Skin contact
 - Product: No data is available on the product itself. ATEmix (acute toxicity estimate of Mixture) > 2,000 mg / kg
 - Components:
 - Carbomonocyclic, alkylated mixtures of poly-aza-alkanes, hydrogenated No data available.
 - Phenol, polymer with formaldehyde: LD 50 (rat): > 2,000 mg / kg Based on the available data, the Classification criteria not met.
 - 3-aminopropyldiethylamine: No data available.
 - Products from reactions of 1,3-benzenedimethanamine with styrene: No data available.
 - Inhalation product: No data is available on the product itself. Based on the available data not classified for acute toxicity.
 - **Acute toxicity**
 - Harmful if swallowed.
 - **Primary irritant effect:**
 - **Skin corrosion/irritation**
 - Causes severe skin burns and eye damage.
 - **Serious eye damage/irritation**
 - Causes serious eye damage.
 - **Respiratory or skin sensitisation**
 - May cause an allergic skin reaction.
 - **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
 - **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
 - **Carcinogenicity** Based on available data, the classification criteria are not met.
 - **Reproductive toxicity** Based on available data, the classification criteria are not met.
 - **STOT-single exposure** Based on available data, the classification criteria are not met.
 - **STOT-repeated exposure** Based on available data, the classification criteria are not met.
 - **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.09.2020

Revision: 28.09.2020

Trade name: **HADALAN EPUni 12E, Komp. B**

(Contd. of page 6)

- **Additional ecological information:**
- **General notes:**
 - Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water
 - Do not allow product to reach ground water, water course or sewage system, even in small quantities.
 - Must not reach sewage water or drainage ditch undiluted or unneutralised.
 - Danger to drinking water if even extremely small quantities leak into the ground.
 - Also poisonous for fish and plankton in water bodies.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
 - **Recommendation**
 - Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- | | |
|-----------------------------------|---|
| · European waste catalogue | |
| 08 01 11* | waste paint and varnish containing organic solvents or other hazardous substances |
- **Uncleaned packaging:**
 - **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- | | |
|--|---|
| · 14.1 UN-Number | UN2735 |
| · ADR, IMDG, IATA | |
| · 14.2 UN proper shipping name | 2735 AMINES, LIQUID, CORROSIVE, N.O.S. mixture, |
| · ADR | ENVIRONMENTALLY HAZARDOUS |
| · IMDG, IATA | AMINES, LIQUID, CORROSIVE, N.O.S. mixture |
| · 14.3 Transport hazard class(es) | |
| · ADR | |
| |   |
| · Class | 8 Corrosive substances. |
| · Label | 8 |
| · IMDG, IATA | |
| |  |
| · Class | 8 Corrosive substances. |
| · Label | 8 |
| · 14.4 Packing group | |
| · ADR, IMDG, IATA | III |
| · 14.5 Environmental hazards: | |
| · Special marking (ADR): | Symbol (fish and tree) |
| · 14.6 Special precautions for user | Warning: Corrosive substances. |

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.09.2020

Revision: 28.09.2020

Trade name: **HADALAN EPUni 12E, Komp. B**

(Contd. of page 7)

· Hazard identification number (Kemler code):	80
· EMS Number:	F-A,S-B
· Stowage Category	A
· Segregation Code	SG35 Stow "separated from" SGGI-acids
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	E
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. MIXTURE, 8, III, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category E2** Hazardous to the Aquatic Environment
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 100 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 200 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- **National regulations:**
- **Waterhazard class:** Water hazard class 3 (Self-assessment): extremely hazardous for water.
- **Other regulations, limitations and prohibitive regulations**
During activities involving exposure to uncured epoxy resins and contact via the skin or the Regular preventive examinations are to be arranged for the respiratory tract.
The product is subject to RL 2004/42 / EG. The EU limit value for this product is in the used state: Cat A / j max. 500 g / l (2010). When used, the product contains: a maximum of 1 g / l VOC.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 28.09.2020

Revision: 28.09.2020

Trade name: HADALAN EPUni 12E, Komp. B

(Contd. of page 8)

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - oral – Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Corr. 1C: Skin corrosion/irritation – Category 1C

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3