



HADALAN® DQ0308 89M

Decorative quartz for decorative surface finishing, 0.3 – 0.8 mm



These pictograms apply to the **basic product**.
Deviations are possible depending on the area of application and processing.

PRODUCT INFORMATION

Description

HADALAN® DQ0308 89M are lightfast, abrasion-resistant decorative quartz crystals for the production of sophisticated floor coverings.

Application

- for the production of decorative interspersed coverings in combination with the respective HADALAN binder

Operational area

- Balcony and terrace areas
- External staircases
- mineral substrates

Place of use

- for interior and exterior use
- in floor areas

Properties

- light-fast
- colour stable
- wear-resistant
- weatherproof

Technical Data

Available container sizes	25 kg/sack
Shade/color tones	grey
Grain	0.3 – 0.8 mm
Storage	dry, 24 months
Consumption	approx. 3 – 4 kg/m ² as a bedding layer

SUBSTRATE



Properties/tests

- The substrate must be stable, surface-dry and free of dirt, dust, cleaning agent residues or other separating substances.
- There is a risk of condensation forming on the substrate surface in the event of significant temperature changes in conjunction with increased humidity. The substrate must be completely dry before starting the coating work. Otherwise, coating damp surfaces may result in peeling or irritation of the material surface.

AREAS OF APPLICATION AND PROCESSING

Applying

- **Bedding layer with HADALAN MBH 12E:** Apply HADALAN MBH 12E as an adhesive layer with approx. 0.3 kg/m². Sprinkle HADALAN DQ0308 89M in excess directly into the fresh adhesive layer, approx. 3 kg/m². After drying, sweep or vacuum off any unbound quartz. Then seal with HADALAN MBH 12E using a mohair roller with approx. 0.5 kg/m².
- **Scatter coating with HADALAN PUR Top 32P transparent:** Apply HADALAN PUR Top 32P transparent as an adhesive layer with approx. 0.3 kg/m². Sprinkle HADALAN DQ0308 89M in excess directly into the fresh adhesive layer, approx. 3 kg/m². After drying, sweep or vacuum off any unbound quartz. Then seal with HADALAN PUR Top 32P transparent using a mohair roller with approx. 0.5 kg/m².

NOTES

System products

- HADALAN® MBH 12E
- HADALAN® EPV 38L
- HADALAN® PUR Top 32P transparent
- Quartz051 57M

To be observed

- Observe the technical data sheets of the system products used.
- Optically related areas must be prepared with material from the same production batch to prevent colour differences.

Ingredients

- Decorative quartzes

Occupational safety / Recommendation

- Further information on safety during transportation, storage and handling can be found in the current safety data sheets.

Disposal

- The following applies to all systems: Only return empty containers to recycling partner Interseroh. Material residues can be disposed of according to EWC code no. 17 09 04 (mixed construction and demolition waste with the exception of those falling under 17 09 01, 17 09 02 and 17 09 03).

Producer

Sievert Baustoffe SE & Co. KG
Mühlenschweg 6, 49090 Osnabrück
Tel. +49 2363 5663-0, Fax +49 2363 5663-90
hahne-bautenschutz.de, info-hahne@sievert.de

The statements are made based on extensive tests and practical experiences. They cannot be applied to every application case. Therefore, we recommend carrying out application trials if necessary. Subject to technical changes in the course of further development. Furthermore, our General Terms and Conditions of Business apply.