



HADALAN® KG 57DD

Plastic granulate for manufacturing anti-slip surfaces



These pictograms apply to the **basic product**.
Deviations are possible depending on the area of application
and processing.

PRODUCT INFORMATION

Description

HADALAN® KG 57DD is a transparent plastic granulate. The particle size is approximately 0.3 to 0.5 mm.

Application

- as an additive to the respective coating system
- for creating anti-slip sealing and protective coatings

Operational area

- Floor surfaces

Properties

- transparent
- universal use
- easy to process
- slip-resistant
- weatherproof

Technical Data

Available container sizes	250 ml/sheet metal bottle
Bulk density	approx. 0.53 kg/l
Storage	dry, 24 months
Consumption	250 g per 6 kg HADALAN LF51 12P 250 g per 5 kg HADALAN Topcoat M 12P 125 g per 2,5 kg HADALAN Topcoat G 32P approx. 5 % by weight for other materials

Applying

- HADALAN KG 57DD is added to the respective coating system and mixed intensively.
- During processing, the mixture must be stirred regularly to prevent HADALAN KG 57DD from settling.
- After mixing, the coating system is applied evenly from the container to the substrate in a crosswise motion using a short pile roller.



NOTES

■ System products

- HADALAN®Reaction resin systems

■ To be observed

- Observe the technical data sheets of the system products used.
- Incorrect application can lead to accumulations and thus to a diffuse surface appearance.
- If the layer thickness is too thick, the anti-slip properties are lost.

■ Ingredients

- Plastic granules

■ Occupational safety / Recommendation

- Further information on safety during transportation, storage and handling can be found in the current safety data sheets.

■ Disposal

- The following applies to all systems: Only return empty containers to recycling partner Interseroh. Material residues can be disposed of in accordance with EWC code no. 17 02 03 (plastic).

■ Producer

Sievert Baustoffe SE & Co. KG

Mühlenschweg 6, 49090 Osnabrück
Tel. +49 2363 5663-0, Fax +49 2363 5663-90
hahne-bautenschutz.de, info-hahne@sievert.de

The statements are made based on extensive tests and practical experiences. They cannot be applied to every application case. Therefore, we recommend carrying out application trials if necessary. Subject to technical changes in the course of further development. Furthermore, our General Terms and Conditions of Business apply.