



HADALAN® MST 89M

Marble stones for decorative surface finishing, 2 – 4 mm



These pictograms apply to the **basic product**.
Deviations are possible depending on the area of application
and processing.

PRODUCT INFORMATION

Description

HADALAN® MST 89M are lightfast, abrasion-resistant stone fractions for the production of sophisticated floor coverings. A special surface treatment of the stones breaks up corners and edges, making them particularly easy to work with.

Application

- for the production of decorative, slip-resistant trowel coatings in combination with the respective HADALAN binder

Operational area

- Balcony and terrace areas
- Indoor floor areas
- External staircases
- mineral substrates

Properties

- light-fast
- colour stable
- abrasion-resistant
- weatherproof
- natural colors

Technical Data

Available container sizes	25 kg/PE bag
Color tone/color tones	anthracite
Grain	2 – 4 mm
Consumption	approx. 12 kg/m ² with 8 mm layer thickness



SUBSTRATE

Properties/tests

- The substrate must be stable, surface-dry and free of dirt, dust, cleaning agent residues or other separating substances.
- There is a risk of condensation forming on the substrate surface in the event of significant temperature changes in conjunction with increased humidity. The substrate must be completely dry before starting the coating work. Otherwise, coating damp surfaces may result in peeling or irritation of the material surface.

AREAS OF APPLICATION AND PROCESSING

Applying

- HADALAN MST 89M is mixed with 3.5 – 7 % binder depending on the area of application. If necessary, carry out preliminary tests.
- The mixed filler mixture is spread evenly over the prepared surface and homogeneously leveled and compacted with a smoothing trowel.
- Please also refer to the processing instructions “Renovation, coating and decorative design with HADALAN PUR liquid plastics”.

NOTES

Cleaning

- Clean tools immediately after use with HADALAN EPV 38L.
- Hardened material can only be removed mechanically.

System products

- HADALAN® BM1K 32P
- HADALAN® LF68 12P
- HADALAN® EPV 38L

To be observed

- When applying and processing system products, the relevant technical data sheets must be observed.
- For further information, please refer to the processing instructions “Renovation, coating and decorative design with HADALAN® PUR liquid plastics”.
- Optically related areas must be prepared with material from the same production batch to prevent colour differences.
- When laying, ensure that the drainage level has a sufficient gradient so that the natural stone covering can drain properly and no puddles form.

Ingredients

- Natural stone

Occupational safety / Recommendation

- No special measures required.

Disposal

- The following applies to all systems: Only return empty containers to recycling partner Interseroh. Material residues can be disposed of according to EWC code no. 17 09 04 (mixed construction and demolition waste with the exception of those falling under 17 09 01, 17 09 02 and 17 09 03).

Producer

Sievert Baustoffe SE & Co. KG
Mühlenschweg 6, 49090 Osnabrück
Tel. +49 2363 5663-0, Fax +49 2363 5663-90
hahne-bautenschutz.de, info-hahne@sievert.de

The statements are made based on extensive tests and practical experiences. They cannot be applied to every application case. Therefore, we recommend carrying out application trials if necessary. Subject to technical changes in the course of further development. Furthermore, our General Terms and Conditions of Business apply.